



### COLORS AVAILABLE

- Neutral
- Black
- Blue
- Green
- Yellow
- Red

### CHEMICAL RESISTANCE

- Oils and fats, fuels, lubricants
- Hydraulic fluids
- Non-chlorine cleaning agents and solvents
- Diluted organic acids
- Very mild mineral acids, bases and salt solutions

### APPLICATION

- Compressed air
- Hydraulics
- Negative pressure
- Cooling lines fuel and lubricant systems

### PROPERTIES

- Wide temperature and application range
- Colour black: UV resistant
- Pressure and impact resistant
- Good chemical resistance
- Smooth surface
- Also available in PA6 (high pressure)

Is available on request in other lengths than the standard coil.

### TECHNICAL SPECIFICATIONS

Temperature Range °C	-40 to + 100
Material	PA

### PRODUCT INFORMATION

Size	P	D	d	s	Bending radius	MOQ	kg/100m
4/2x1	44	4.00	2.00	1.00	15.0	100m	0.970
5/3x1	33	5.00	3.00	1.00	30.0	100m	1.140
6/4x1	26	6.00	4.00	1.00	27.0	100m	1.620
6/4x1	26	6.00	4.00	1.00	27.0	500m	1.620
6.35/4.35x1	26	6.35	4.35	1.00	27.0	100m	1.810
8/6x1	19	8.00	6.00	1.00	40.0	100m	2.270
10/8x1	19	10.00	8.00	1.00	60.0	50m	2.910
10/7x1.5	24	10.00	7.00	1.50	45.0	50m	3.540
12/10x1	12	12.00	10.00	1.00	85.0	50m	4.000
12/9x1.5	19	12.00	9.00	1.50	70.0	50m	5.100
15/12x1.5	15	15.00	12.00	1.50	100.0	50m	6.570

Bar= operating pressure at 23 °C

- MOQ = Minimum order quantity
- P = pressure (bar)
- D = tube outside diameter (mm)
- d = tube inside diameter (mm)
- s = wall thickness (mm)

